

PRZEBUDOWA DROGI GMINNEJ
CHOROBEL - JANOWIEC
Wykaz długości boków i azymutów

Nr punktu	X	Y	długość	odległość	pa ra me.	łuk	długość redukcji	Długość po redukcji	azymut
A	5539139.29	4447362.80	54.81	0	t	17.10	0.00	0.00	9.01.02
B	5539193.42	4447371.39		54.81	dl dl/2	32.32 16.16	-0.94	53.87	
B	5539193.42	4447371.39	64.45	53.87	t	17.10	0.00	53.87	55.18.32
C	5539230.10	4447424.38		118.31	dl dl/2	32.32 16.16	-0.94	117.37	
C	5539230.10	4447424.38	102.11	117.37	t	9.78	0.00	117.37	54.34.28
D	5539289.29	4447507.59		219.48	dl dl/2	19.56 9.78	0.00	219.48	
D	5539289.29	4447507.59	384.81	219.48	t	18.13	0.00	219.48	53.49.41
E	5539516.41	4447818.23		604.29	dl dl/2	36.22 18.11	-0.02	604.27	
E	5539516.41	4447818.23	18.56	604.27	t	18.52	0.00	604.27	63.53.26
F	5539524.58	4447834.90		622.83	dl dl/2	36.62 18.31	-0.21	622.62	
F	5539524.58	4447834.90	254.10	622.62	t	10.17	0.00	622.62	91.06.10
G	5539519.69	4448088.95		876.72	dl dl/2	19.95 9.98	-0.19	876.53	
G	5539519.69	4448088.95	435.52	876.53	t	30.20	0.00	876.53	91.42.33
H	5539506.70	4448524.28		1312.05	dl dl/2	60.28 30.14	-0.06	1311.99	
H	5539506.70	4448524.28	341.79	1311.99	t	102.87	0.00	1311.99	83.09.28
I	5539547.42	4448863.64		1653.79	dl dl/2	205.60 102.80	-0.07	1653.72	
I	5539547.42	4448863.64	195.23	1653.72	t	72.67	0.00	1653.72	80.22.55
J	5539580.04	4449056.13		1848.95	dl dl/2	145.32 72.66	-0.01	1848.94	

Parametry łuków

Nr P.	R	t	z	dl
B	40	17.098	3.219	32.316
D	1500	9.778	0.032	19.556
E	95	8.355	0.365	16.668
F	42	10.169	1.179	19.954
H	400	30.198	1.135	60.283
I	3000	72.674	0.880	145.319